



HIGH EFFICIENCY MOTOR

Produces less noise and better savings.



SELF DIAGNOSTIC

Provides code that identify issue to address.



VARIABLE SPEED

Energy efficient and more even temperature throughout the area.



REMOTE CONTROLLED

Gives more accessibility and convenience.



Slimpac Floor Mounted Aircon

FEATURES





Easy access filter

Washable PU foam is accessible by just removing the return grille.

Smart Display

Indicates the operation status and error code for easier diagnosis for repair.

Sleep Mode

The set temperature rises 1°C every hour, it will not exceed beyond 30°C and after 2 hours, the rising will stop.

Eco Mode

The unit will run at low fan and stopped if it reaches the set temperature. It will turn on again after the ambient temperature is above the set temperature after a certain period of time.

Wide Angled Two-Direction Airflow

Adjustable vertical louver using remote and horizontal louver manually or swing button up to 30° up and down to evenly and quickly cool the area.

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATION | | | |
|-------------------------------------|-------------|------------------------------|------------------------------|
| CAPACITY | | 4.0 hp | 6.0 hp |
| PRODUCT CODE | Set | CAR SET DFE-ASD 04.0H REM VS | CAR SET DFE-ASD 06.0H REM VS |
| TECHNICAL DATA | | | |
| Cooling Capacity | kJ/hr | 37,000 (13,100 - 39,000) | 52,500 (18,800 - 53,500) |
| Power Consumption | Watts | 3,900 (1,480 - 4,400) | 5,300 (1,800 - 5,500) |
| Energy Efficiency Ratio (EER) | kJ/W-hr | 9.5 (8.9 - 8.9) | 9.9 (10.4 - 9.7) |
| Sound Level Indoor (Hi, Mid, Low) | dBa | 61/ 58 / 55 | 58/54/52 |
| Power Supply | Vz/Ph/H | 230 / 1 / 60 | 230 / 1 / 60 |
| Refrigerant Type | | R410A | R410A |
| PHYSICAL DATA | | | |
| Indoor Dimensions (WxHxD) | mm | 508 x 1,806 x 288 | 580 x 1,750 x 430 |
| Indoor Packaging Dimensions (WxHxD) | mm | 590 x 1,910 x 382 | 670 x 1,870 x 525 |
| Indoor Weight (Net/Gross) | kg | 42.5 / 46 | 62.5 / 66.5 |
| Outdoor Dimension (WxHxD) | mm | 936 x 722 x 336 | 936 x 722 x 336 |
| Outdoor Packaging Dimension (WxHxD) | mm | 1,074 x 765 x 415 | 1,075 x 765 x 415 |
| Outdoor Weight (Net/Gross) | kg | 91 / 94 | 95 / 97.5 |
| PIPING | | | |
| Pipe Sizes (Liquid/Gas) | mm Φ | Ф9.52 / Ф15.9 | Ф9.52 / Ф19.1 |
| Max Pipe Length | m | 30 | 50 |

Follow us on Social Media

www.fb.com/CarrierPhilippines

www.instagram/carrier_ph

www.carrier.com.ph

customerservice@ccac.com.ph

Talk to us:
0917 842 5555
(02) 8883 5555 (Motr

(02) 8883 5555 (Metro Manila) Toll free (Nationwide) 1-800-10-888-8888 (PLDT)

Best After Sales Guarantee

5-YEAR COMPRESSOR WARRANTY

1-year warranty on parts and labor, additional 4 years warranty on compressor.

WIDEST SERVICES NETWORK

With more than 200 service centers nationwide

ORIGINAL PARTS AVAILABLE

Original parts are always available. Even old units can be good as new.

NOTES

- . Product information and specifications in the brochure have been obtained under specific testing conditions and are applicable on the data publication only.
- 2. Product information and specifications are subject to change without notice due to continuous product development and improvement.
- 3. Concepcion-Carrier Air Conditioning Company (CCAC) does not warrant accuracy of all product information and specifications contained herein.
- 4. CCAC shall not be liable of any claim of error, omission or misinterpretation in relation to the information and specifications contained herein, or for any loss or damage resulting from reliance on such information or specification.